

Technical Specifications

Sensor / Transmitter

Working Temperature	(-20°C--85°C) -4° F to 185° F
Working Humidity	0 – 95%
Dimensions	(23 x 21 x 21 mm) .8” x .8” x .9”
Weight	(9g) 0.3 oz
Battery Voltage	3V DC (CR1632)
Battery Life	1 year
Standby Current	500nA
Working Current	6mA
Pressure Range JET-400C	(0 Bar – 10 Bar) 0 – 145 psi
Pressure Range JET-300C	(0 Bar – 4.5 Bar)0-65 psi
Pressure Precision JET-400C	(±0.3 Bar) ± 4 psi
Pressure Precision JET-300C	(±0.1 Bar) ± 1.5 psi
Temperature Range	(-20°C -- 85°C) -4°F to 185° F
Temperature Precision	(± 3°C) ± 5° F
Signal Transmitting Frequency	433.92 MHz
Operating Distance	up to 20M (65 ft) Booster recommended If towing or over 25 ft (Receiver to rear Tire)

Monitor / Receiver

Working Voltage	3V DC
Working Temperature	(-20°C -- 60°C) -4°F to 140°F
Working Humidity	0 – 90%
Standby Current	0.1mA
Working Current	15mA
Dimensions	90 x 55 x 24 mm 3.5”x2.2”x0.9”
Signal Receiving Frequency	433.92 MHz
Color of Backlight	White